

## Product Description

### CANON RF 550DII Rotary Filmer

For years, the world's leading financial institutions have relied on Canon microfilm technology to provide a reliable and highly secure audit trail for checks and daily work. Designed to meet the demanding needs of today's banking industry, the compact Rotary Filmer 550 DII turns high-speed recording into a simple task.

#### Specifications:

Type:	Desktop rotary microfilmer with built-in camera unit
Reproduction Ratio:	42x, Canon lens MC 20mm
Filming Mode:	Duplex
Film Supply:	16mm -100 ft. (30.5m), or thin base 125/215 ft. film
Film Take-up:	Standard 93mm dia. reel
Document Size:	Width: 5-1/8" - 9-1/6"(130 - 230mm) Length: 2-3/8" - 4-11/16"(70 - 120mm) Thickness: 0.002" - 0.01"(0.05 - 0.3mm)
Conveyor Speed:	138 ft./min. (42m/min.)
Feeder:	Auto feeder with gap adjustment and side guide
Stacker:	Adjustable guide for back/forward and left/right positions
Endorser:	Optional B100 Endorser; Fixed stamping position by single-impression type Die Drum 232 w/6-digit dater Optional Ink roller: Red, Black, Blue and Purple
Dimensions:	(H x W x D):11"x 19-3/8"x 24-9/16"
Weight:	52 lb. (24 kg)



# Canon

**Quiet and Reliable** The RF 550 DII is engineered for noise-free operation and measures a mere 19"x 25", so its presence is hardly noticeable. And keeping the unit well-maintained and clean is a simple operation, thanks to easy-to-reach optical parts and a built-in microcomputer which displays self-diagnosis codes when necessary to ensure trouble-free, reliable operation.



Datrue Process Automation | 2705 Twin City Drive | Mandan, ND 58554 | 701-663-8930 | 800-279-7493  
Branch Offices Located in Fargo, North Dakota, and Billings, Montana

[www.datrue.com](http://www.datrue.com)