

## Product Description

### Maverick M-360 Exception Item Encoder Series

With minimal space and training requirements, the economically priced Maverick MICR III encoder offers the optimal solution for exception item encoding.

The MICR III is completely field programmable through the keyboard.

The 2-line display helps minimize errors by prompting the operator. The first line allows for descriptions and/or instructions and the second line displays the operator's entry. These features help ensure data accuracy, thus making the MICR III extremely easy to learn and use.

#### SPECIFICATIONS

Dimensions:Length:12.5inches (31.75 cm)Width:8.0inches (20.32 cm)Height:3.75inches ( 9.53 cm)

Weight:4.25 pounds (1.93 kg)

Display:16 character, 2-line, alphanumeric•

M-360 – Standard non-backlit LCD Display

M-366 – High Intensity LCD wide-angle display

Ribbon:Low volume cartridge with average yieldof 30,000 characters

Power:120 VAC, wall mount transformer240 VAC, in-line

Memory:Non-Volatile, Flash ROM

Encode 65 character/full field Capability

Options:Eject and Catch Tray available on both M-360 and M-366



Datrue Process Automation | 2705 Twin City Drive | Mandan, ND 58554 | 701-663-8930 | 800-279-7493  
Branch Offices Located in Fargo, North Dakota, and Billings, Montana

[www.datrue.com](http://www.datrue.com)